



Endeavor[®]

IO-505, IO-605 & IO-805

5 1/4" 2-way Indoor/Outdoor Loudspeakers

6 1/2" 2-way Indoor/Outdoor Loudspeakers

8" 2-way Indoor/Outdoor Loudspeakers

IO-505

- ◀ 5 1/4" 2-way acoustic suspension indoor/outdoor loudspeaker
- ◀ 5 1/4" Dupont[®] Kevlar woofer with butyl rubber surround
- ◀ 40 Hz - 21,000 Hz
- ◀ 50 Watts nom. 100 Watts max
- ◀ Available in White (IO-505W) & Black (IO-505B)

IO-605

- ◀ 6 1/2" 2-way acoustic suspension indoor/outdoor loudspeaker
- ◀ 6 1/2" Dupont[®] Kevlar woofer with butyl rubber surround
- ◀ 38 Hz - 21,000 Hz
- ◀ 60 Watts nom. 120 Watts max
- ◀ Available in White (IO-605W) & Black (IO-605B)

IO-805

- ◀ 8" 2-way acoustic suspension indoor/outdoor loudspeaker
- ◀ 8" Dupont[®] Kevlar woofer with butyl rubber surround
- ◀ 35 Hz - 21,000 Hz
- ◀ 70 Watts nom. 140 Watts max
- ◀ Available in White (IO-805W) & Black (IO-805B)

Features

Sealed, port-less design enclosure prevents bugs and moisture from entering cabinet

Rust Proof Grilles are austenitic stainless steel which are acid bathed and passivated prior to being epoxy painted for long life in high humidity and salt air environments

1" Tetoron[®] soft dome pivoting tweeters

Indoor/outdoor bass equalization

8 Ohms

90 dB sensitivity

Versatile mounting options, includes standard type "U" bracket, and mounting bosses on rear for optional double-swivel mounting brackets

Suitable for use on book shelves with bracket-less finished look



Dimensions

IO-505 Enclosure: 7 1/4" W x 10" H x 7 1/2" D
mounting bracket increases depth 3/4"

IO-605 Enclosure: 8 3/4" W x 11 3/8" H x 8 5/8" D
mounting bracket increases depth 1"

IO-805 Enclosure: 10 5/8" W x 13 3/4" H x 10 5/8" D
mounting bracket increases depth 1 1/4"

Weights

IO-505 Shipping: 16 lbs pair
Net: 5.75 lbs each

IO-605 Shipping: 22 lbs pair
Net: 8.1 lbs each

IO-805 Shipping: 32 lbs pair
Net: 11.15 lbs each

Versatile Mounting Options

The Endeavor IO-505, 605, & 805 come with two sets of end-caps for a finished look every time



Notched end-cap



Elegant cover conceals and protects connection terminals



Shown with included U-Bracket



Solid end-cap



Bookshelf configuration



Threaded inserts for optional aluminum double-swivel bracket



Exclusively distributed in Oceania by
Jay Vee Technologies Pty Ltd
www.jayveetechnologies.com.au
sales@jayveetechnologies.com.au



1135 S. Rock Blvd. Suite #310,
Reno, Nevada 89502-7168
www.oemsystems.com